

SPECIFICATIONS

INPUT	3 x PC Input (*D-Sub 15pin) 3 x PC-Audio (*3.5mm) 1 x C-Video (*RCA) 1 x Stereo Audio (*RCA) 1 x Stereo Audio (*2.54mm connector, feedback from projector) 1 x Microphone (*3.5mm) 1 x Microphone (*6.3mm)
--------------	--

OUTPUT	2 x VGA Output (*standard 2.54mm connector for Projector) 1 x VGA output (*D-Sub 15pin for monitor) 2 x C-Video (*standard 2.54mm connector) 1 x Main Stereo Audio (*standard 2.54mm connector) 2 x Tx (*standard 2.54mm connector)
---------------	---

VGA BANDWIDTH	3-in 3-out VGA Matrix Switcher Distribution Amplifier (900MHz R+G+B)
----------------------	--

MAX. RESOLUTION	1280 x 1024
------------------------	-------------

ALL CABLE LENGTH	Up to 28 meter
-------------------------	----------------

CONFIGURABLE COM PORT	1:2 x RS-232 (8 Data Bit and 1 Stop Bit) Baud Rate (1200 to 115200) Parity Bit (Non, Even or Odd) Programmable projector protocol
------------------------------	--

DELAY TIME	Projector "ON/OFF" delay time (*in sec) 1 to 99
-------------------	---

CONTROL BUTTON	Number of user defined "Control Button" x 8 Available protocol for each "Control Button" x 2
-----------------------	---

VIDEO SELECTION	All Video / VGA Switching	Digital
------------------------	---------------------------	---------

AUDIO SELECTION	Audio Switching	Digital
------------------------	-----------------	---------

VOLUME	Main Volume Control	Analog
---------------	---------------------	--------

MIC. GAIN	Microphone Input Gain Control	Analog
------------------	-------------------------------	--------

POWER ADAPTOR	12V-DC
----------------------	--------

MECHANICAL

HOUSING	ABS enclosure
----------------	---------------

DIMENSIONS (L x W x H)	149 x 88 x 48 mm (Standard UK two gang casing)
-------------------------------	--


WEIGHT	350g
---------------	------

PACKAGE INCLUDE

- 1 x Controller unit
- 1 x 12 V DC Power adaptor
- 1 x User Manual

Multimedia Controller Switcher

Programmable Integrated Projector Controller Switcher



Model: AVS-313

PRODUCT DESCRIPTION

The **ABtUS AVS-313** Media Control Panel is one of the most user friendly and installer friendly, preprogrammed controller specifically designed for a easy and central control of any two projection system as well as a monitor out. It removes the need for over-complicated and multiple remote control handsets. With the 3x3 VGA/Audio matrix switching, user are now free to project any VGA image to any output display (monitor, projector 1 and projector 2) accordingly. Ideal for Lab or training room with dual projection application.

PRODUCT HIGHLIGHTS

- “User Programmable” with Window base Application Software
- Simple to used with one to one function controlled button
- Fully self contained / integrated Projector Controller with AV switcher VGA Matrix switching
- Supports 3x3 VGA matrix switching with resolutions from VGA to SXGA
- Easy Installation with standard 2.54mm connector and cabling

TYPICAL APPLICATION

Any professional presentation system requiring dual projection and dual projector controller switching.

- Schools (Media Classroom)
- Churches
- Corporate Applications (Training Room)

CONFIGURATION DIAGRAM

